

Fluid Warming Cabinet



Application

Heating applications include warming of liquid medicine, nutrient solution, rinsing liquid and physiological saline. Installations can be found in operating rooms, ICU, emergency rooms, wards and other related areas.

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



Haier Biomedical
International



Haier Biomedical
International

Product Features



Fast heating speed

Variable power PTC heating module with fast heating speed and energy saving



UV sterilization

UV light sterilization in the cabinet with a variety of optional sterilization methods for effective prevention of possible contamination



Multiple overheat protections

Electronic control + mechanical temperature control + overheat protection, multiple temperature control to ensure heating safety



Environmentally friendly

No compressor or external fan, extremely quiet with no disturbance to the airflow in the operating room and no effect on temperature, reduces risks of cross-contamination



Product Advantages

- Fast and efficient heating
- Standard UV sterilization for effective sterilization and other sterilization options available
- Multiple over heating protections to ensure product viability
- Two-sensor



Ergonomic Design


- Large and clear 7-inch LCD touch screen
- Easy to clean stainless steel interior and flat external surfaces
- Multiple alarms for over-heating protection



Internal Structure



7 Inch LCD Screen



UV Sterilization Lamp

Specifications

	Model	HYR-111	
Technical Data	Cabinet Type	Upright, One Glass Door	
	Climate Class	SN	
	Warming Type	Forced Air Warming	
	Sound Level (dB(A))	42	
Performance	Temperature Range (°C)	26°C~50°C, Above Ambient Temperature	
Control	Controller	Microprocessor	
	Display	LCD Touch Screen	
Electrical Data	Power Supply (V/Hz)	220-240/50/60	
	Power(W)	130	
	Power Consumption (kWh/24h)	0.59	
Dimensions	Capacity (L/Cu.Ft)	111/3.9	
	Net/Gross Weight (approx)	kg	58/68
		lbs	127.6/149.6
	Interior Dimensions (W*D*H)	mm	477*528*462
		in	18.67*20.67*18.1
	Exterior Dimensions (W*D*H)	mm	597*682*833
		in	23.37*26.7*32.61
	Packing Dimensions (W*D*H)	mm	700*775*960
		in	27.6*30.5*37.8
	Container load (20'/40'/40'H)	46/94/94	
Alarms	High/Low Temperature	Y	
	Sensor Error	Y	
	Door Ajar	Y	
Accessories	Caster	Y	
	Foot	Y	
	Porthole	Y	
	Shelves	Y	